



IKE STEEL

Shirley Zhao

Phone: +86 15670614009

Email: shirley@ikesteel.com

ADD: A8-711 LuoYang Hengsheng Technology Park, Luolong District, LuoYang -471000, HeNan , China



IKE STEEL (Luoyang) Co., Ltd

2025

PERGOLA
Product Catalog



IKE STEEL



IKESTEEL

CONTENTS

Type -145

Type -175

Type -200

Type -220

Windproof Roller Shutter

Sliding Glass Door


Aluminum Shutters

Retractable Electric Louver pergola


Project Presentation

TYPE 145

- ✓ Aluminum construction with long service life
- ✓ Maximum load up to 100 kg/m²
- ✓ Easy to build with assembly instructions
- ✓ Integrated roof gutter
- ✓ Aluminum blades
- ✓ Supports the installation of LED lights



Manual Type




Motor Type

Type-145 pergola is a semi-permanent aluminum pergola with single-layer innovative louvres to provide a shade outdoor area for all of common residential outdoor area. With the maximum 90-degree manual and motor louvre system, you can have the louvres opened or closed easily. It's 100% waterproof, comes with an internal gutter system; it can withstand wind rating 112 km/h.

TYPE 145

Aluminum waterproof blades, stronger and better.

Motor type



Freedom between the opening and closing, fully show the aesthetics of life.

Louver/Blade

Size: 145*32*1.3mm

Post

Size: 135*135*2.0mm

Beam/Frame

Size: 150*130*1.8mm

● MOTORIZED



Motorised with light



Better heat insulation




Double-layer louver



Detailed Dimension Introduction

The dimensions of the frame/blade/post



Wind Load: 112 km/h
Snow Load: 100 kg/m²
Safety: Hidden drains and electrical lines


Type-145

FUNCTIONAL FEATURES


Sun-proof, Waterproof, Ventilated

It's adopted a new generation of shading technology, which has a very good function of shading and rain protection.


By flexibly adjusting the opening and closing state of the blades, you can also adjust the light and ventilation effectsand choose the best way to start outdoor leisure life. It can withstand wind rating 112km/h.



Rainproof, snow-proof, windproof




Sun-proof, Anti-UV




Ventilated



Closed



Flexible adjustment of opening and closing angle



Open

DRAINAGE SYSTEM


Hidden drainage system, no fear of heavy rain.

Beam and gutter are integrated to achieve a more perfect waterproof function.

Rainwater stream through the internal gutter system and to posts of the structure which is a practical and clever solution.




Hidden drainage system



Water being flowed into post





Drain to the lower end of the post




Blade grooves facilitate diversion

CONTAINER LOADING CAPACITY

| Photos | Size | Carton size(mm) | | | N.W (Kg) | G.W (Kg) | QTY (CTN) | CTN NO | CBM | Description | 20GP | 40GP | 40HQ |
|---|------|-----------------|-----|-----|-------------|-------------|--------------|-----------|------|-----------------|------|------|------|
| | | L | W | H | | | | | | | | | |
|  | 3X3 | 2990 | 245 | 230 | 180 | 230 | 1 | 1/4 | 0.16 | Beam +Gutter | 32 | 68 | 77 |
| | | 2910 | 310 | 310 | | | 1 | 2/4 | 0.27 | Louver | | | |
| | | 2910 | 310 | 310 | | | 1 | 3/4 | 0.27 | Louver | | | |
| | | 2415 | 260 | 280 | | | 1 | 4/4 | 0.14 | Post+hand crank | | | |
|  | 3X4 | 4000 | 250 | 230 | 240 | 290 | 1 | 1/4 | 0.25 | Beam +Gutter | 25 | 55 | 60 |
| | | 2920 | 320 | 390 | | | 1 | 2/4 | 0.36 | Louver | | | |
| | | 2920 | 320 | 390 | | | 1 | 3/4 | 0.36 | Louver | | | |
| | | 2430 | 320 | 270 | | | 1 | 4/4 | 0.16 | Post+hand crank | | | |

TYPE 175



● **Manual Type**

- ✓ Aluminum construction with long service life
- ✓ Maximum load up to 120 kg/m²
- ✓ Easy to build with assembly instructions

- ✓ Integrated roof gutter
- ✓ Aluminum blades
- ✓ Supports the installation of LED lights



● **Motor Type**

Type-175 pergola is a semi-permanent premium aluminum pergola with Aluminum innovative louvers, posts with round corner design led lighting system to provide a perfect shade for your outdoor area. It is made of high-quality aluminum, which guarantees durability and solidity of the structure. Adjustable top blades allow you to choose between sun and shade seating, Adopt 135mm posts, stable structure with affordable cost, great waterproof effect.

TYPE 175

Aluminum waterproof blades, stronger and better.

Motor



Freedom between the opening and closing, fully show the aesthetics of life.

Louver/Blade

Size: 175*40*1.6mm

Post

Size: 135*135*2.0mm

Beam/Frame

Size: 180*130*2.0mm

● MOTORIZED



Motorised
with light



Better heat
insulation




Double-layer
louver



Detailed Dimension Introduction

The dimensions of the frame/blade/post



Blade : 175*40*1.6mm

Frame : 180*130*2mm

Post : 135*135*2.0mm


Wind Load: 120 km/h
Snow Load: 120 kg/m²
Safety: Hidden drains and electrical lines

Type-175

FUNCTIONAL FEATURES

Sun-proof, Waterproof, Ventilated


It's adopted a new generation of shading technology, which has a very good function of shading and rain protection.
By flexibly adjusting the opening and closing state of the blades, you can also adjust the light and ventilation effects, and choose the best way to start outdoor leisure life. It can withstand wind rating 28m/s (100 km/h).



DRAINAGE SYSTEM





Hidden drainage system, no fear of heavy rain.

Beam and gutter are integrated to achieve a more perfect waterproof function. Rainwater stream through the internal gutter system and to posts of the structure which is a practical and clever solution.



OPTIONAL ACCESSORIES

CONTAINER LOADING CAPACITY

| Photos | Size | Carton Size (mm) | | | N.W (Kg) | G.W (Kg) | QTY (CTN) | CTN NO | CBM | Description | 20GP | 40GP | 40HQ |
|---|------------------|------------------|-----|-----|----------|----------|-----------|--------|-----|-------------|------|------|------|
| | | L | W | H | | | | | | | | | |
|  | 3X3 | 2900 | 340 | 220 | 225 | 275 | 1 | 1/4 | 0.2 | Beam+Gutter | 29 | 65 | 65 |
| | | 2900 | 350 | 310 | | | 1 | 2/4 | 0.3 | Louver | | | |
| | | 2900 | 350 | 310 | | | 1 | 3/4 | 0.3 | Louver | | | |
| | | 2750 | 300 | 260 | | | 1 | 4/4 | 0.2 | Post | | | |
|  | 3X4 | 2955 | 310 | 160 | 300 | 350 | 1 | 1/4 | 0.2 | Beam+Gutter | 18 | 44 | 52 |
| | | 2910 | 350 | 410 | | | 1 | 2/4 | 0.4 | Louver | | | |
| | | 2910 | 350 | 410 | | | 1 | 3/4 | 0.4 | Louver | | | |
| | | 2750 | 360 | 260 | | | 1 | 4/4 | 0.3 | Post | | | |
|  | 4X4 | 4010 | 310 | 300 | 400 | 450 | 1 | 1/6 | 0.4 | Beam+Gutter | 14 | 37 | 42 |
| | | 1970 | 370 | 395 | | | 1 | 2/6 | 0.3 | Louver | | | |
| | | 1970 | 370 | 395 | | | 1 | 3/6 | 0.3 | Louver | | | |
| | | 1970 | 370 | 395 | | | 1 | 4/6 | 0.3 | Louver | | | |
| | | 1970 | 370 | 395 | | | 1 | 5/6 | 0.3 | Louver | | | |
| | | 2800 | 330 | 260 | | | 1 | 6/6 | 0.2 | Post | | | |
|  | 6X4 (Two bay) | 4035 | 440 | 220 | 600 | 650 | 1 | 1/6 | 0.4 | Beam+Gutter | 10 | 24 | 25 |
| | | 2880 | 350 | 405 | | | 1 | 2/6 | 0.4 | Louver | | | |
| | | 2880 | 350 | 405 | | | 1 | 3/6 | 0.4 | Louver | | | |
| | | 2880 | 350 | 405 | | | 1 | 4/6 | 0.4 | Louver | | | |
| | | 2880 | 350 | 405 | | | 1 | 5/6 | 0.4 | Louver | | | |
| | | 2920 | 415 | 250 | | | 1 | 6/6 | 0.3 | Post | | | |

TYPE 175

Customization is supported, with free choices and combinations available

TYPE 200

- ✓ Aluminum construction with long service life
- ✓ Maximum load up to 140 kg/m²
- ✓ Easy to build with assembly instructions



- ✓ Integrated roof gutter
- ✓ Double top blades
- ✓ Supports the installation of LED lights



Type-200 pergola is a semi-permanent premium aluminum pergola with double-layer innovative louvers, posts with round corner design, led lighting system to provide a perfect shade for your outdoor area. It is made of high-quality aluminum, which guarantees durability and solidity of the structure. Adjustable top blades allow you to choose between sun and shade seating. It can withstand wind rating 125 km/h.

TYPE 200

Aluminum waterproof blades, stronger and better.



Freedom between the opening and closing, fully show the aesthetics of life.

Louver/Blade

Size: 200*40*1.8mm

Post

Size: 150*150*2.0mm

Beam/Frame

Size: 200*130*2.0mm

● **MOTORIZED**



Motorised
with light



Better heat
insulation



Double-layer
louver

Open Effect Display

Enjoy every ray of morning sunshine



Detailed Dimension Introduction


The dimensions of the frame/blade/post




Tail-end bearing drive




LED lamp



Blade : 200*40*1.8mm



Frame : 200*130*2mm




Post : 150*150*2.0mm

Wind Load: 125 km/h
Snow Load: 140 kg/m²
Safety:Hidden drains and electrical lines


Type-200

FUNCTIONAL FEATURES


Sun-proof, Waterproof, Ventilated



Rainproof, snow-proof, windproof



Sun-proof, Anti-UV




Ventilated



Closed




Flexible adjustment of opening and closing angle



Open

DRAINAGE SYSTEM

Hidden drainage system, no fear of heavy rain.




Hiddend rainage system



Drain to the lower end of the post







Water being flowed into post



Blade grooves facilitate diversion

CONTAINER LOADING CAPACITY

| Photos | Size | Carton Size (mm) | | | N.W (Kg) | G.W (Kg) | QTY (CTN) | CTN NO | CBM | Description | 20GP | 40GP | 40HQ |
|---|-------------------|------------------|-----|-----|----------|----------|-----------|--------|------|-------------|------|------|------|
| | | L | W | H | | | | | | | | | |
|  | 3X3 | 2870 | 320 | 160 | 252 | 302 | 1 | 1/4 | 0.15 | Beam+Gutter | 24 | 49 | 55 |
| | | 2870 | 370 | 270 | | | 1 | 2/4 | 0.29 | Louver | | | |
| | | 2870 | 370 | 270 | | | 1 | 3/4 | 0.29 | Louver | | | |
| | | 2780 | 360 | 270 | | | 1 | 4/4 | 0.27 | Post | | | |
|  | 3X4 | 3900 | 320 | 160 | 336 | 386 | 1 | 1/4 | 0.20 | Beam+Gutter | 19 | 43 | 48 |
| | | 2870 | 370 | 340 | | | 1 | 2/4 | 0.36 | Louver | | | |
| | | 2870 | 370 | 340 | | | 1 | 3/4 | 0.36 | Louver | | | |
| | | 2780 | 360 | 270 | | | 1 | 4/4 | 0.27 | Post | | | |
|  | 4X4 (Two bays) | 3890 | 340 | 200 | 448 | 498 | 1 | 1/6 | 0.26 | Beam+Gutter | 13 | 36 | 42 |
| | | 1960 | 330 | 380 | | | 1 | 2/6 | 0.25 | Louver | | | |
| | | 1960 | 330 | 380 | | | 1 | 3/6 | 0.25 | Louver | | | |
| | | 1960 | 330 | 380 | | | 1 | 4/6 | 0.25 | Louver | | | |
| | | 1960 | 330 | 380 | | | 1 | 5/6 | 0.25 | Louver | | | |
| | | 2780 | 310 | 260 | | | 1 | 6/6 | 0.22 | Post | | | |
|  | 6X4 (Two bay) | 3980 | 380 | 200 | 672 | 722 | 1 | 1/6 | 0.26 | Beam+Gutter | 8 | 24 | 27 |
| | | 2930 | 330 | 340 | | | 1 | 2/6 | 0.25 | Louver | | | |
| | | 2930 | 330 | 340 | | | 1 | 3/6 | 0.25 | Louver | | | |
| | | 2930 | 330 | 340 | | | 1 | 4/6 | 0.25 | Louver | | | |
| | | 2930 | 330 | 340 | | | 1 | 5/6 | 0.25 | Louver | | | |
| | | 2760 | 380 | 250 | | | 1 | 6/6 | 0.22 | Post | | | |
| | | | | | | | | | | | | | |

TYPE 200

TYPE 220



- ✓ Aluminum construction with long service life
- ✓ Maximum load up to 160 kg/m²
- ✓ Easy to build with assembly instructions



- ✓ Integrated roof gutter
- ✓ Double top blades
- ✓ Supports the installation of LED lights



Type-200 Peraola 2.0 features 150mm square posts and wider double-louver louvers to withstand extreme weather, including heavy snow and strong winds. Built from high-quality aluminum, it offers dimmable RGB LED lighting, perimeter lighting, and full waterproofing with a water-electricity separated post for added safety. Supporting both freestanding and wall-mounted setups, the adjustable louvers provide flexible shading, withstanding winds up to 130 km/h.

TYPE 220

Aluminum waterproof blades, stronger and better.



Freedom between the opening and closing, fully show the aesthetics of life.

Louver/Blade

Size: 200*40*1.8mm

Post

Size: 150*150*2.0mm

Beam/Frame

Size: 200*150*2.4mm

● **MOTORIZED**



Motorised
with light



Better heat
insulation



Double-layer
louver


Open Effect Display

Enjoy every ray of morning sunshine




Detailed Dimension Introduction

The dimensions of the frame/blade/post




Tail-end bearing drive




Wind Load: 130 km/h
Snow Load: 160 kg/m²
Safety: Hidden drains and electrical lines




LED lamp



Blade : 200*40*1.8mm



Frame : 200*150*2.4mm




Post : 150*150*2.0mm


Type-220

FUNCTIONAL FEATURES


Sun-proof, Waterproof, Ventilated




Rainproof, snow-proof, windproof



Sun-proof, Anti-UV



Ventilated



closed




Flexible adjustment of opening and closing angle



Open

DRAINAGE SYSTEM


Hidden drainage system, no fear of heavy rain.




Hiddend rainage system



Water being flowed into post



Drain to the lower end of the post



Blade grooves facilitate diversion

CONTAINER LOADING CAPACITY

| Photos | Size | Carton Size (mm) | | | N.W (Kg) | G.W (Kg) | QTY (CTN) | CTN NO | CBM | Description | 20GP | 40GP | 40HQ |
|--------|------|------------------|-----|-----|----------|----------|-----------|--------|------|-------------|------|------|------|
| | | L | W | H | | | | | | | | | |
| | 3X3 | 3050 | 450 | 210 | 270 | 320 | 1 | 1/4 | 0.29 | Beam+Gutter | / | 36 | 45 |
| | | 2910 | 430 | 360 | | | 1 | 2/4 | 0.47 | Louver | | | |
| | | 2930 | 420 | 260 | | | 1 | 3/4 | 0.33 | Louver | | | |
| | | 2850 | 450 | 340 | | | 1 | 4/4 | 0.47 | Post | | | |
| | 3X4 | 3980 | 470 | 210 | 360 | 410 | 1 | 1/4 | 0.3 | Beam+Gutter | / | 28 | 35 |
| | | 2920 | 420 | 460 | | | 1 | 2/4 | 0.6 | Louver | | | |
| | | 2920 | 420 | 350 | | | 1 | 3/4 | 0.47 | Louver | | | |
| | | 3100 | 450 | 156 | | | 1 | 4/4 | 0.47 | Post | | | |
| | 4X4 | 4070 | 470 | 200 | 480 | 530 | 1 | 1/4 | 0.3 | Beam+Gutter | / | 24 | 30 |
| | | 3970 | 420 | 460 | | | 1 | 2/4 | 0.61 | Louver | | | |
| | | 3940 | 420 | 350 | | | 1 | 3/4 | 0.47 | Louver | | | |
| | | 2850 | 450 | 156 | | | 1 | 4/4 | 0.47 | Post | | | |
| | 4x6 | 5740 | 480 | 200 | 720 | 770 | 1 | 1/5 | 0.32 | Beam+Gutter | / | 18 | 22 |
| | | 3950 | 420 | 460 | | | 1 | 2/5 | 0.58 | Louver | | | |
| | | 3940 | 420 | 350 | | | 1 | 3/5 | 0.46 | Louver | | | |
| | | 3940 | 420 | 350 | | | 1 | 4/5 | 0.46 | Louver | | | |
| | | 2850 | 450 | 306 | | | 1 | 5/5 | 0.47 | Post | | | |
| | 4x8 | 4070 | 710 | 230 | 960 | 1010 | 1 | 1/6 | 0.5 | Beam | / | 13 | 17 |
| | | 3940 | 420 | 450 | | | 1 | 2/6 | 0.58 | Louver | | | |
| | | 3940 | 420 | 450 | | | 1 | 3/6 | 0.58 | Louver | | | |
| | | 3940 | 420 | 370 | | | 1 | 4/6 | 0.47 | Louver | | | |
| | | 3940 | 420 | 370 | | | 1 | 5/6 | 0.47 | Louver | | | |
| | | 3100 | 540 | 340 | | | 1 | 6/6 | 0.4 | Post | | | |
| | | | | | | | | | | | | | |

TYPE 220

Retractable Electric Pergola



- ✓ Aluminum construction with long service life
- ✓ Maximum load up to 120 kg/m²
- ✓ Easy to build with assembly instructions
- ✓ Integrated roof gutter
- ✓ Double top blades
- ✓ Windproof 10-Level, SGS Certified



● MOTORIZED



Motorised
with light



Better heat
insulation



Double-layer
louver

Retractable Electric Louver Pergola is an upgraded version, Double-layer louvres with added LED strip lighting and rubber seals for improved waterproofing. Built for harsh environments, it withstands strong winds and heavy snow with durable aluminum construction. The pergola supports freestanding or wall-mounted installations and includes 150mm square posts with separated water and electricity. Adjustable louvers allow easy control between sun and shade, withstanding wind speeds up to 120 km/h.

Retractable Pergola

Double-layer waterproof blades, stronger and better heat insulation.



Freedom between the opening and closing, fully show the aesthetics of life.

Post
Size:150x150x2.0mm

Operation
Motorized


Louver
Size:200x40x1.8mm

Beam with built-in gutter (motorized)
Size:230x150x2.5mm




FUNCTIONAL FEATURES


Sun-proof, Waterproof, Ventilated




Rainproof, snow-proof, windproof



Sun-proof, Anti-UV



Ventilated



Closed




Flexible adjustment angle



Open

DRAINAGE SYSTEM

Hidden drainage system, no fear of heavy rain.




Hiddend rainage system



Water being flowed into post








Drain to the lower end of the post








Blade grooves facilitate diversion



CONTAINER LOADING CAPACITY

| Photos | Size | Carton Size (mm) | | | N.W (Kg) | G.W (Kg) | QTY (CTN) | CTN NO | CBM | Description | 20GP | 40GP | 40HQ |
|---|------|------------------|-----|-----|----------|----------|-----------|--------|------|-------------|------|------|------|
| | | L | W | H | | | | | | | | | |
|  | 3X3 | 3050 | 450 | 210 | 270 | 63 | 1 | 1/4 | 0.29 | Beam+Gutter | / | 36 | 45 |
| | | 2910 | 430 | 360 | | 54 | 1 | 2/4 | 0.47 | Louver | | | |
| | | 2930 | 420 | 260 | | 37 | 1 | 3/4 | 0.33 | Louver | | | |
| | | 2850 | 450 | 340 | | 72 | 1 | 4/4 | 0.47 | Post | | | |
|  | 3X4 | 3980 | 470 | 210 | 360 | 410 | 1 | 1/4 | 0.3 | Beam+Gutter | / | 28 | 35 |
| | | 2920 | 420 | 460 | | | 1 | 2/4 | 0.6 | Louver | | | |
| | | 2920 | 420 | 350 | | | 1 | 3/4 | 0.47 | Louver | | | |
| | | 3100 | 450 | 156 | | | 1 | 4/4 | 0.47 | Post | | | |
|  | 4X4 | 4070 | 470 | 200 | 480 | 530 | 1 | 1/4 | 0.3 | Beam+Gutter | / | 24 | 30 |
| | | 3970 | 420 | 460 | | | 1 | 2/4 | 0.61 | Louver | | | |
| | | 3940 | 420 | 350 | | | 1 | 3/4 | 0.47 | Louver | | | |
| | | 2850 | 450 | 156 | | | 1 | 4/4 | 0.47 | Post | | | |
|  | 4x6 | 5740 | 480 | 200 | 720 | 770 | 1 | 1/5 | 0.32 | Beam+Gutter | / | 18 | 22 |
| | | 3950 | 420 | 460 | | | 1 | 2/5 | 0.58 | Louver | | | |
| | | 3940 | 420 | 350 | | | 1 | 3/5 | 0.46 | Louver | | | |
| | | 3940 | 420 | 350 | | | 1 | 4/5 | 0.46 | Louver | | | |
| | | 2850 | 450 | 306 | | | 1 | 5/5 | 0.47 | Post | | | |
|  | 4x8 | 4070 | 710 | 230 | 960 | 1010 | 1 | 1/6 | 0.5 | Beam | / | 13 | 17 |
| | | 3940 | 420 | 450 | | | 1 | 2/6 | 0.58 | Louver | | | |
| | | 3940 | 420 | 450 | | | 1 | 3/6 | 0.58 | Louver | | | |
| | | 3940 | 420 | 370 | | | 1 | 4/6 | 0.47 | Louver | | | |
| | | 3940 | 420 | 370 | | | 1 | 5/6 | 0.47 | Louver | | | |
| | | 3100 | 540 | 340 | | | 1 | 6/6 | 0.4 | Post | | | |
| | | | | | | | | | | | | | |

PRODUCT SUMMARY

| | TYPE 145 | TYPE 175 | TYPE 200 | TYPE 220 | Retractable |
|---------------------|---|---|---|--|---|
| Comparison |  |  |  |  |  |
| Louvre | Double | Double | Double | Double | Double |
| Post | 135x135x2.0mm | 135x135x2.0mm | 150x150x2.0mm | 150x150x2.0mm | 150x150x2.0mm |
| Wind resistance | ✓ | ✓ | ✓ | ✓ | ✓ |
| Waterproof | ✓ | ✓ | ✓ | ✓ | ✓ |
| Sunshading | ✓ | ✓ | ✓ | ✓ | ✓ |
| Motorised | ✓ | ✓ | ✓ | ✓ | ✓ |
| Manual | ✓ | ✓ | Not Recommended | Not Recommended | Not Recommended |
| Led lighting | ✓ | ✓ | ✓ | ✓ | ✓ |
| Installation method | Freestanding & Wall mounted | Freestanding & Wall mounted | Freestanding & Wall mounted | Freestanding & Wall mounted | Freestanding & Wall mounted |



FREE-STANDING TYPE



WALL-MOUNTED TYPE

OPTIONAL ACCESSORIES

Customization is supported, with free choices and combinations available


Windproof Roller Shutter

Manual Blind , Manual zip Blind and Motorized zip Blind, offering a personalized service of excellent quality.The structure is powder coating aluminum and its fabric can be imported acrylic canvas Dickson brand, mesh type, transparent imported PVC or other special choice.Support manual operation without zipper, manual operation with zipper for tighter fabric effect and Motorised button-operated with zipper for satisfying different applications and offering the maximum possibility for end users.

closed




closed



open



open



Manual Zip Blind IK-910A

| | |
|-------------|-------------------|
| Cassette | 100 X 100 X 2.0mm |
| Rail | 49 X 39 X1.2mm |
| Bottom bar | 45 X 25.4 X 1.5mm |
| Roller tube | dia 70mm |
| Operation | manual |

Motorized Zip Blind IK-910B

| | |
|-------------|-------------------|
| Cassette | 120 X 120 X 2.0mm |
| Rail | 60 X 39 X1.5mm |
| Bottom bar | 56 X 25.4 X 2mm |
| Roller tube | dia 78mm |
| Operation | motorized |

Sliding Glass Door

Equisit 8mm tempered sliding glass with side aluminum profile is perfect match for pergola to form a relax private space.It can realize a variety of scene functions such as cool summer and warm winter, dustproof and transparent scenes, making outdoor leisure life more comfortable and more quality.



Framed Glass




Frameless Glass

1



2



Glass

Tempered glass 8mm

Side Border

35x18.7x2.0mm

Side Rail

88x30x1.4mm

Mid Border

44x35x2.0mm

Up Rail

83x60x1.4mm

Up/Down Border

35x32.7x2.0mm

Down Rail

88x8.2x1.2mm



2

Frameless Glass

1

Framed Glass

Windproof Roller Shutter

Aluminum Shutter is an innovative accessory that offers a privacy wall option and the ability to block sunlight in outdoor living space under the pergola. Fixed panels,sliding panels and bi-folding panels are available. High-grade aluminum material and premium powder coating make this sleek overall look and resistant to rust. It is a great addition to outdoor pergola and let through the breeze and enjoy a nature outdoor time.



Bi-folding panels



Fixed panels



Siding panels

| | |
|---|-----------|
| Double - track Hanging Rail: | 2.142KG/M |
| Cover Plate of Double - track Hanging Rail: | 0.131KG/M |
| Frame of Louver: | 0.584KG/M |
| Cover Plate of Louver Frame: | 0.131KG/M |
| Aluminum Strip for Louver Transmission: | 0.131KG/M |
| Blade of Hand - flip Louver: | 0.633KG/M |
| Frame of Hand - flip Louver: | 0.962KG/M |
| Opposite Frame for Hand - flip: | 0.440KG/M |
| Angle Aluminum 38*25: | 0.44KG/M |
| Bottom Rail of Sliding Door: | 0.706KG/M |

Standard color in stoc

Custom Color Support
More than 200 RAL colors are available



RAL9005




RAL9016




RAL7016



RAL8017



JET BLACK
RAL9016



TRAFFIC WHITE
RAL9016



ANTHRACITE GREY
RAL7016



DARK BROWN
RAL8017



PRODUCT PICTURE

SCIENTIFIC DESIGN AND INGENUITY



IKE STEEL

IKE STEEL (Luoyang) Co., Ltd





IKE STEEL



Global Sales Network Distribution



20+
PROFESSIONAL
MANUFACTURER

76+
SALES COUNTRY
QUANTITY

24391+
SERVICE COMPANIES AND
CUSTOMERS

*Have established sales and service centers in multiple cities across the country
Products are exported to many overseas countries and have won unanimous praise from foreign customers!*



IKE STEEL (Luoyang) Co., Ltd

Shirley Zhao

Phone: +86 15670614009

Email: shirley@ikesteel.com

ADD: A8-711 LuoYang Hengsheng Technology Park,
Luolong District, LuoYang -471000, HeNan , China

